

G24A2718 en

Product data

algemeen

Reference No.	G24A2718 en
Mat. thickness mm	2.50
RAL color	9006
Load / kg	425
load indication at speed	20 km/h
Recommended tyre size	5.00-8
Ø Mittenloch (A), Ø Bolzenlochkreis (B) und Bolzenlochzahl (C)	60/100/4
(A) Diameter centre hole mm	60
(B) Pitch circle diameter mm	100
(C) Number of studholes	4
(C) Stud hole diameter mm	13.5
Gatvorm	600
Rim size	3.00Dx8
Mat. thickness mm	2.00
RAL color	3002
Load / kg	725
load indication at speed	20 km/h
Recommended tyre size	5.00-8
Ø Mittenloch (A), Ø Bolzenlochkreis (B) und Bolzenlochzahl (C)	60/100/4
(A) Diameter centre hole mm	60
(B) Pitch circle diameter mm	100
(C) Number of studholes	4
(C) Stud hole diameter mm	13.5
Gatvorm	600
Rim size	3.00Dx8

Company Information

Vlukon is located in Vaals, the centre of Western Europe. Near Maastricht and 5.5 km west of the centre of Aachen (Germany).

postal address:

Selzerbeeklaan 6
6291 HW Vaals
+31 43 306 2941
Chapter No. 14620421

visit address:

Selzerbeeklaan 6
6291 HW Vaals
info@vlukon.com
www.vlukon.com

